

DATA
OUTPUT

BASIC
MODEL

ULTRASONIC THICKNESS GAGE CODE ISU-200D



- Measure the thickness from one side of object, suitable for pipe, tank, etc.
- Applicable material: metal, plastic, glass, nylon, resin, ceramic, rubber, ice
- Low and high limits with judgement
- Memory of maximum 500 readings

SPECIFICATION

Resolution	0.01mm (range<100mm)
	0.1mm (range≥100mm)
Accuracy	±0.05mm (range<10mm)
	±(0.01+0.5%H)mm (range≥10mm) H is the thickness to be measured in mm
Velocity	1000-9999m/s
Power supply	3×AAA batteries
Dimension	151×70×24mm
Weight	200g

STANDARD DELIVERY

Main unit	1pc
Transducer ISU-200D-N05	1pc
Couplant	1 bottle
USB cable and software	1pc

OPTIONAL ACCESSORY

Transducer	ISU-200D-N02
	ISU-200D-N07
	ISU-200D-W05
	ISU-200D-HT5

SPECIFICATION OF TRANSDUCERS

Code	Frequency	Diameter (Ød)	Measuring range	Minimum size of pipe for measurement (diameter × wall thickness)	Applicable temperature	Application
ISU-200D-N05	5.0MHz	12mm	0.8~300mm	25×3mm	<60°C	general use
ISU-200D-N02	2.0MHz	17mm	2~400mm	30×4mm	<60°C	for casting steel
ISU-200D-N07	7.5MHz	8mm	0.75~40mm	15×1.2mm	<60°C	for thin material
ISU-200D-W05	5.0MHz	10mm	0.8~230mm	20×1.2mm	<60°C	for wall thickness
ISU-200D-HT5	3.0MHz	15mm	3~100mm	25×3mm	<300°C	for high temperature