# **Air Plug Gauge**



# **RANGE: 1.5 - 250 mm**



#### **FEATURES**

- Quick and easy checking of bore
- Standard 2 jets for checking size, taper,
- 3 jets at 120 degree for average size & tri-lobed effect (for diameter 6 mm & above)
- With extensions to check deeper bores
- Can be supplied to check through or blind bores
- Can be supplied with multiple jets
- Hard chrome plated for extended life
- Can be supplied with carbide sleeve on request
- For specific depth or land width checking, adjustable depth collars can be provided

# **SPECIAL APPLICATIONS**



#### **BRACKET MOUNTED AIR PLUG**

Air plugs can be bracket mounted for independent and easy checking of small components



#### **RIGHT ANGLE ATTACHMENT**

Right angle attachment can be provided for checking of bores in restricted areas



#### **EXTENSIONS**

Extensions in lengths of 25 mm/50 mm/100 mm/200 mm can be provided for deeper bores as required





#### AIR PLUG WITH CARBIDE SLEEVE

Air plug with carbide sleeve for



# **BENCH MOUNTED AIR PLUG GAUGE**

Air plugs can be bench mounted for easy checking of components



### **MULTILEVEL AIR PLUG GAUGE**

Air plugs can be made with jets at multi-level to check the component at different level to check taper



# **FLAT AIR PLUG GAUGE**

Special flat air plug can be used for checking groove width i.e. the grooves of piston



#### AIR PLUG WITH DEPTH COLLAR

Air plugs can be provided with depth collar for measurement of diameter at a fixed distance from face

