

DIGITAL TORQUE WRENCH

- Clockwise and counter-clockwise operation
- Unit: N.m, in.lb, ft.lb, kg.cm
- Peak and track working mode
- Target torque value can be set, with audible and visible alarm:
 - Green LED light on and buzzer sounds when torque value is 90%~100% of target torque
 - Both green and red LED light on and buzzer sounds when target torque value is reached
- Power off automatically in 5 minutes without any operations
- Non-slip grip handle
- With overload record (once the torque reaches 110% of the maximum range)



IST-W135A

SPECIFICATION

| Code | Range | Accuracy | Resolution | Square driver (L) | Power supply | Length | Weight |
|------------|-------------|--|------------|-------------------|----------------|--------|--------|
| IST-W30A | 6~30N.m | clockwise: $\pm 2\%$ counter-clockwise: $\pm 3\%$ | 0.01N.m | 1/4" | 2×AA batteries | 390mm | 830g |
| IST-W135A | 27~135N.m | | 0.1N.m | 3/8" | | 415mm | 950g |
| IST-W200A | 40~200N.m | | 0.1N.m | 1/2" | | 530mm | 1.4kg |
| IST-W340A | 68~340N.m | | 0.1N.m | 1/2" | | 650mm | 1.6kg |
| IST-W500A | 100~500N.m | clockwise: $\pm 2.5\%$ counter-clockwise: $\pm 3.5\%$ | 0.1N.m | 3/4" | | 950mm | 2.1kg |
| IST-W850A | 170~850N.m | | 0.1N.m | 3/4" | | 1220mm | 2.55kg |
| IST-W1200A | 240~1200N.m | | 1N.m | 1" | | 1800mm | 13kg |
| IST-W1500A | 300~1500N.m | | 1N.m | 1" | | 1800mm | 13kg |
| IST-W2000A | 400~2000N.m | | 1N.m | 1" | 1800mm | 14kg | |

OPTIONAL ACCESSORY

Calibration cable

IST-W-CABLE