

Metrix+™

Innovative Excellence

Electrical & Electronic Test Measuring Instruments
Net Dealer's Price List Effective 16 July 2019

Page - 1 of 4

Sr	Digital Anemometer, HSN : 9031	Unit Price
1	AVM 01 (0.3~30M/S & Air Temperature 0~50°C Fan type Built in Probe, Pocket Type)	1000
2	AVM 03 (0.4~30M/S & Air Temperature 0~60°C/32~140°F) Fan type Vane Probe	2250
3	AVM 05 (0.4~45M/S CMM, CFM & Air Temperature 0~60°C/32~140°F) Fan type Vane Probe	2700
4	PC Interface RS 232C Software + USB Adaptor for AVM 05	3000
Digital Power Guard (Micro Power Monitor), HSN : 9030		
5	PG-08 Large backlight LCD Watt/CUR/Volt/Freq/EC/CO2/PF displayed in sequence	1040
Digital Clamp on Power Meter, HSN : 9030		
6	3510PW Trus RMS (AC-1000A) Data Logger, 9999 Auto Range, 55mm Jaw Caliber	7500
Digital Clamp Meter - AC, HSN : 9030		
7	125A (1999 digit, AC-600A, Resistance, Frequency, Diode, Continuity, APO)	750
8	125A+ (1999 digit, AC-600A, backlight LCD, Resistance, Diode, Continuity, Data Hold)	800
9	225A (3999 digit, AC-400A, Resistance, Frequency, Capacitance, Temperature, Diode)	1150
10	1250A (1999 digit, AC-1000A, Resistance, Diode, Continuity, Data Hold, APO)	1150
11	2250T True RMS Inrush (AC-3¼-1000A, Resistance, Capacitance, Frequency, Duty)	1625
Digital Clamp Meter - AC/DC, HSN : 9030		
12	725A (3999 digit, AC/DC-600A, Resistance, Frequency, Capacitance, Temperature)	1790
13	725A+ True RMS (5999 digit, AC/DC-600A, Resistance, Frequency, Capacitance, Temp.)	2250
14	4250T True RMS (3999 digit, AC/DC-1000A, Resistance, Frequency, Capacitance, Temp.)	2750
15	36 True RMS 15 in 1 (AC/DC - 400A, Resistance, Frequency, Capacitance, Duty, Diode)	4500
16	2003A (3999 digit, 2000A-AC/DC, Resistance, Frequency, Capacitance, Duty, Diode)	7500
17	Kaise Japan SK-7708 True RMS (2000A-AC/DC)	7650
Digital Coating Thickness Gauge (DFT Meter), HSN : 9017		
18	Coat Gauge F (1800um) Only Ferrous, Integrated Probe	5625
19	Coat Gauge FN+ (1300um) Fe+nFe, dot matrix display, Alarm facility, 80 readings can store	8125
20	Coat Measurer F (1250um) Only Ferrous	8500
21	Coat Measurer F+N (1250um) Ferrous/non-Ferrous Combine	11250
22	Coat Scope-I (2000um Integrated Probe) Ferrous/non-Ferrous Combine	15000
23	Coat Scope 27 (2000um) Ferrous/non-Ferrous Combine	15500
24	Coat Scope 27-4K (4000um) Ferrous/non-Ferrous Combine	19250
25	Coat Scope 27-5K (5000um) Ferrous/non-Ferrous Combine	21875
26	Spare Calibration Foil Set	1500
27	Spare Probe "F"	2500
28	Spare Probe 2 in 1 "F" & "nFe" combine	3000
29	PC Interface RS 232C Software + USB Adaptor	4000
Digital Distance Meter, HSN : 9031		
30	DM 20A (UL) (0.3~20m) Metric/Imperial Measurement	1590
31	DM 40 (LA) (0.3~40m) Metric/Imperial Measurement	1750
32	DM 60 (LA) (0.3~60m) Metric/Imperial Measurement	3000
33	DM 80 (LA) (0.3~80m) Metric/Imperial Measurement	3500
34	DM 100 (LA) (0.3~100m) Metric/Imperial Measurement	3625
Non-Contact Voltage Tester (Pen Type), HSN : 9030		
35	CD 2 Non-Contact AC Voltage Line Tester (24V~600V)	240
36	CX 1 3 in 1 Pen type PHASE Sequence, Line Finder, Neon Electroscope Tester	460

Metrix+™

Innovative Excellence

Page -2 of 4

Sr	Digital Rubber Hardness Tester, HSN : 9024	Unit Price
37	SHORE "A" RHT-A (0~100A/10~90H Soft Rubber/Felt)	11560
38	SHORE "D" RHT-D (0~100D/10~90H Hard Rubber/Plastic)	14250
	Digital Metal (Leeb) Hardness Tester, HSN : 9024	
39	Hardmaster-P (170~960HLD, HV, HB, HRC, HRB, HRA, HS, directly print with mini printer)	23750
40	Hard Master (integrated probe 200~900HLD, HRB, HRC, HV, HB, HS,HL)	30750
41	MI-970 (External probe 200~900HLD, HL, HRC, HRB, HB, HV, HS, HL)	30000
42	130 (170~960HLD, HRB, HRC, HV, HB, HS, HL)	35500
43	Curvature Ring Set for HARDMASTER	8200
44	Impact Device 'D' (Probe) for MI 970	7400
45	Impact Device 'D' (Probe) for 130	19000
46	Mini Printer for Hardmaster-P	8000
47	PC Interface RS 232C Software + USB Adaptor	4000
	Digital Earth Resistance Tester, HSN : 9030	
48	DET 1501 (20/200/2000Ω, 3½ Digit Max. 1999, Auto Range 0~2000Ω)	4750
49	DET 1503 (20/200/2000Ω, Heavy duty Measuring Range, 0.00~20Ω/ 0.0~200Ω/ 0~2000Ω)	8000
	Digital Insulation Tester (Megger), HSN : 9030	
50	DIT 918 (100V/250V/500V/1000V/2500V-50GΩ)	2500
51	Hi Voltage Insulation Tester DIT 954 (1000V/2500V/5000V-20GΩ)	5375
52	Hi Voltage Insulation Tester DIT 3125A (Economical Model) (500V/1000V/2500V/5000V)	10000
53	Hi Voltage Insulation Tester DIT 3125 (500V/1000V/2500V/5000V-1000GΩ)	18750
	Digital Lux Meter (Illuminometer), HSN : 9027	
54	Lx 101A (1~2,00,000 Lux, FC built in Photo Electric Sensor, Pocket Type)	1000
55	Lx 101 (1~50,000 Lux, Photo Electric Sensor)	1125
56	Lx 1330A (1~1,00,000 Lux, Built in Sensor)	1500
57	Lx 1336A (0~5,00,000 Lux, 0~20,000 FC, Separate Light Sensor, PC interface)	4250
	Digital Moisture Meter, HSN : 9031	
58	MM 2 (Pocket Type, 2%~40%, with 8 selection Range, Multi Purpose)	690
59	MM 2A+ (Pocket Type, 2%~70%, 4 Range Multi Purpose with Temperature & RH)	1320
60	MM-Wa (2%~70%, 4 Range, Multi-Purpose, Temperature & RH, Dual Probe)	3125
61	MM-W (High Accuracy 0%~80%, Multi-Purpose, 10 selection ranges, Dual Long Probe)	5000
62	MM-S (High Accuracy 0%~80%, Multipurpose, 20 range, Non-Contact Moisture Meter)	5510
63	MM-S+ (0%~80%, wide Application, Multipurpose Dual Probe 0%~80%, 10 range selection)	5625
64	MM-Soil (High Accuracy 0%~80%, Wide measuring range and high resolution)	8125
65	GMM 7002A (5%~30%, 4 species selection, Grain Moisture Meter, Hi-Lo alarm setting)	2750
66	MM-G (High Accuracy, Grain Moisture Meter, 6%~30%, 36 Species Selection)	5250
67	MM-GC (High Accuracy, Grain Moisture Meter, 22 species selection, 0%~50% Cup Type)	8125
	Analog Multimeter, HSN : 9030	
68	HC 260TR (TR test, AC/DC Volt DCA 2.5mA~10A, Ohm, -10DB~62DB NPN & Diode check)	750
	Digital Multimeter, HSN : 9030	
69	9A (3¾ digit, backlight, LCD display, ACV/DCV, DCA, Resistance, Diode)	520
70	31 (3½ digit backlight LCD display ACV/DCV, DCA, Resistance, Diode, Continuity, Bat. Test)	500
71	31C (3½ digit, backlight, LCD display, ACV/DCV, DCA, Resistance, Diode, Continuity, Temp.)	570
72	603 (3½ digit, ACV/DCV, ACA/DCA, Resistance, Diode, Continuity, hFe Transistor, APO)	580
73	603A (3½ digit, ACV/DCV, ACA/DCA, Resistance, Capacitance, Frequency, Diode, Temp.)	710
74	14xL (3½ digit, ACV/DCV, ACA/DCA, Resistance, Capacitance, Frequency, Diode, Temp.)	1060
75	451xL (Panel Calibrate, LCR Multimeter, 3½ digit, Resistance, Capacitance, Frequency)	1325
76	16xL (6000 Analog Bar graph, Resistance, Capacitance, Frequency)	1855
77	171 True RMS (ACV/DCV, 6000 Count, Resistance, Capacitance, Temperature, Frequency)	1500
78	18 True RMS (3 6/7, ACA/ACV, 6000 Count, Resistance, capacitance, frequency, duty)	1625
79	DM 620 True RMS (50000 Count-Data Logger, 18000 point Data memory, 10Mhz Frequency)	9000

Metrix+™

Innovative Excellence

Page -3 of 4

Digital Sound Level Meter, HSN : 9027		Unit Price
80	SL 4001 (30~130db, Fast/ Slow weighing A & C)	2250
81	SL 4005 (30~130db, A & C or "F", Fast/ Slow Weighting, P C Interface Compatible)	2750
82	PC Interface RS 232C Software + USB Adaptor for SL 4005	3000
Digital Surface Roughness Tester, HSN : 9031		
83	SURFTEST 10 (Ra:0.05-10.00um, Rz:0.020-100.0um)	40000
84	MICROSURF 10A (Ra:0.05-10.00um, Rz:0.020-100.0um)	41000
85	Precision Referance Standard (Test Piece) STEEL for MICROSURF 10A & SURFTEST 10	4800
86	Precision Referance Standard (Test Piece) GLASS for MICROSURF 10A & SURFTEST 10	8400
87	Standard Sensor for MICROSURF 10A & SURFTEST 10	16000
88	Extension Adaptor for MICROSURF 10A & SURFTEST 10	6500
89	PC Interface RS 232 Software + USB Data Interface Cable	4000
Digital Gloss Meter, HSN : 9031		
90	GLS 09 (0.1~200 Gloss Units, Resolution 0.1 Gloss Units, 200GU)	9000
91	GLS 09M (20°/60°/85° Combine Degrees Measuring Geometry, 200GU)	14375
92	Micro Gloss (20°/60°/85° Multi Angle, High Precision, Data Logger, 1000 GU range)	40500
93	PC Interface Software + USB Data Interface cable for Gloss Meter	4000
Digital Infrared Thermometer, HSN : 9025		
94	FH 1 Human Body Infrared Thermometer (30°C~45°C)	2750
95	MT 2A (-32°C~320°C, DS 12:1, Emissivity 0.95 fixed)	750
96	MT 2C (-50°C~380°C, DS 12:1, Emissivity 0.95 fixed, Color Display)	875
97	MT 4 (-50°C~550°C, DS 12:1, Emissivity 0.95 fixed)	930
98	MT 4xL (-32°C~550°C, DS 12:1, Emissivity 0.95 fixed, Gift box+Carry case)	1000
99	MT 4A (-50°C~600°C, DS 12:1, Emissivity 0.1~1.00 Adjustable)	2125
100	MT 4A+ (-50°C~750°C, DS 12:1, Emissivity 0.10~1.00 Adjustable)	2300
101	MT 12A (-50°C~1150°C, DS 20:1, Emissivity 0.10~1.00 Adjustable)	4560
102	MT 14 (-50°C~1350°C, DS 50:1, Emissivity 0.1~1 Adjustable)	8125
103	MT 16 (-18°C~1650°C, DS 50:1, Emissivity 0.10~1.00 Adjustable)	8750
104	MT 18 (-30°C~1850°C, DS 50:1, Emissivity 0.10~1.00 Adjustable)	16750
105	MT 22 (200°C~2500°C, DS 80:1, Emissivity 0.1~1 Adjustable)	23750
Digital Thermo-Humidity Meter (Thermo Hygrometer), HSN : 9025		
106	TH 01 (-10°C~70°C, Humidity 20%~90% RH Indoor)	275
107	TH 01 In-Out (-10~70°C Indoor, -50~70°C Outdoor, Humidity 20%~90% RH)	625
108	HT 3006 (-40°C~1400°C, Humidity 5%~90% RH, 'K' Probe)	1125
109	HT 9A (Data Logger, Dual Display, LCD -30~80°C, 0%~100% Dew point pick up)	3375
110	HT 9 (Large Back light, LCD Wet Bulb -10~60°C, 10%~95%, RH 10%~95%)	2500
Digital Tachometer, HSN : 9029		
111	DT 2234 B (Non-Contact Laser, 2.5~99,999RPM)	1040
112	DT 2234 BL (Non-Contact Laser with Backlit Display, 2.5~99,999RPM)	1000
113	DT 2235 B (Contact Tachometer, 0.5~19,999RPM)	1440
114	TM 1000xL (Non-Contact Laser Tachometer, 999 second Counter, 0.5~99,999RPM)	1170
115	TM 4005 (Contact/Non-Contact Combine)	2500

Metrix+™

Innovative Excellence

Page -4 of 4

Sr	Analog Tachometer, HSN : 9029	Unit Price
	Digital Ultrasonic Thickness Gauge, HSN : 9017	
116	UTG 5 (1.2 ~ 220mm, Resolution 0.1mm)	6250
117	UTM 5A (1.2 ~ 225mm, Resolution 0.1mm)	6750
118	UTM 5 (1 ~ 200mm, Resolution 0.1mm)	8875
119	UTM 9 (0.9~350mm, Resolution 0.01mm)	11375
120	UTG 27 (1~400mm, Resolution 0.01mm)	13000
121	UTM 18CT (0.65~600mm, Resolution 0.01mm) through Coating Thickness	31500
122	Spare Probe Standard for UTM 5/UTM 9/UTG 27	2600
123	Spare Probe 6mm for UTM 5/UTM 9/UTM 5A/UTG 27	3200
124	High Temperature Ceramic Probe for UTM 5/UTM 9/UTG 27	8000
125	Spare Probe for UTM 18CT (1.0-600mm Thickness Probe) No 5	4000
126	Spare Probe for UTM 18CT (3-30mm Through Coating Probe) P 5EE	3500
127	Spare Probe for UTM 18CT (0.65-200mm Thickness Probe) No 7	4000
128	PC Interface RS 232C Software + USB Adaptor for UTM 5 & UTM 9	2600
129	PC Interface RS 232C Software for UTM 18CT	4200
130	Calibration Step Block for Ultrasonic Thickness Gauge 4 Steps	9000
	Digital Vibration Meter(Accelerometer), HSN : 9031	
131	VM 8200P (Portable Shear Type, Velocity, Acceleration & Displacement, 10Hz~15KHz)	8750
132	VM 8200+ (Velocity, Acceleration & Displacement, 10Hz ~10kHz)	12000
133	VM 8200+MK II (Velocity, Accele., Displacement, RPM & Frequency, 10Hz ~10kHz)	15500
134	VB 8202A (Velocity, Accele., Displacement, RPM & Frequency, 1Hz ~ 10kHz)	17500
135	PC Interface RS 232C Software + USB for VM 8200+/VM 8200+mk II/VB 8202A	4000
136	Spare Probe for Vibration Meter	5200
137	Spare Attachment rare Earth Powerful Magnet /Stinger Probe Spherical / Cone	3000
138	Spare Piezo Electric Pin Probe for VM 8200+/VM 8200+mk II/ VB 8202A	8000
	Digital Capacitance Meter, HSN : 9030	
139	DCM 1501 (0.1pF~20,000 µF, 9 steps 200pF ~ 20mF)	925
	Digital Angle Gauge, HSN : 9017	
140	Angle Gauge AG 900 Working range angle: 0°~225° Angle precision: ±0.5°, Resolution: 0.1°. 400mm with Horizontal & Vertical Glass bubble can be used as Spirit Level	1810
	Pocket Thickness Gauge, HSN : 9017	
141	Peacock Brand JAPAN Mod: PS 1 0-20mm x0.1mm	3600
142	Peacock Brand JAPAN Mod: CS 10 0-10mm x 0.01mm	5400
	Digital Stroboscope, HSN : 9029	
143	DT 2239 (50~12000FPM, Internal / external triggering fast conversion; x2 and ÷2 button)	6750
144	DT 2259A (50~40000FPM, Internal / external triggering fast conversion; x2 and ÷2 button)	7200