



Metrixplus Instruments - w.e.f.-01/01/2018

Sr	Digital Anemometer	Unit Price
1	AVM 01 (0.3~30M/S & Air Temperature 0~50°C Fan type Built in Probe, Pocket Type)	2200
2	AVM 03 (0.4~30M/S & Air Temperature 0~60°C/32~140°F) Fan type Vane Probe	4500
3	AVM 05 (0.4~45M/S CMM, CFM & Air Temperature 0~60°C/32~140°F) Fan type Vane Probe	5750
4	PC Interface RS 232C Software + USB Adaptor for AVM 05	4600
Digital Power Guard (Micro Power Monitor)		
5	PG-08 Large backlight LCD Watt/CUR/Volt/Freq/EC/CO2/PF displayed in sequence	2800
Digital Clamp on Power Meter		
6	3510PW Trus RMS (AC-1000A) Data Logger, 9999 Auto Range, 55mm Jaw Caliber	12200
Digital Clamp Meter - AC		
7	125A (AC-600A)	1330
8	125A+ (AC-600A)	1540
9	225A (3¾-AC-400A)	2030
10	1250A (AC-1000A)	2400
11	2250 (3¾-Auto-AC-1000A)	3000
12	2250T True RMS Inrush (AC-3¾-1000A)	3250
Digital Clamp Meter - AC/DC		
13	725A (3¾-AC/DC-600A)	4000
14	725A+ True RMS (AC/DC-600A)	4500
15	4250T True RMS Inrush Digital (AC/DC-3¾-1000A)	5800
16	36 True RMS 15 in 1 (AC/DC - 400A)	9500
17	2003A (2000A-AC/DC)	14000
18	Kaise Japan SK-7708 True RMS (2000A-AC/DC)	15500
Digital Coating Thickness Gauge (DFT Meter)		
19	Coat Gauge F (1800um) Only Ferrous Integrated Probe	13850
20	Coat Gauge F+N (1500um) Ferrous/non-Ferrous Combine Integrated Probe	15500
21	Coat Measurer F (1250um) Only Ferrous	16500
22	Coat Measurer F+N (1250um) Ferrous/non-Ferrous Combine	21000
23	Coat Scope-I (2000um Integrated Probe) Ferrous/non-Ferrous Combine	29500
24	Coat Scope 27 (2000um) Ferrous/non-Ferrous Combine	31500
25	Coat Scope 27-4K (4000um) Ferrous/non-Ferrous Combine	35000
26	Coat Scope 27-5K (5000um) Ferrous/non-Ferrous Combine	38200
27	Spare Calibration Foil Set	2600
28	Spare Probe "F"	5000
29	Spare Probe 2 in 1 "F" & "nFe" combine	6500
30	PC Interface RS 232C Software + USB Adaptor	6000
Digital Distance Meter		
31	DM 20A (UL) (0.3~20m) Metric/Imperial Measurement	3240
32	DM 40 (LA) (0.3~40m) Metric/Imperial Measurement	3800
33	DM 60 (LA) (0.3~60m) Metric/Imperial Measurement	6800
34	DM 80 (LA) (0.3~80m) Metric/Imperial Measurement	8200
35	DM 100 (LA) (0.3~100m) Metric/Imperial Measurement	9800
Non-Contact Voltage Tester (Pen Type)		
36	CD 2 Non-Contact AC Voltage Line Tester (24V~600V)	540
37	CX 1 3 in 1 Pen type PHASE Sequence, Line Finder, Neon Electroscope Tester	950



Metrixplus Instruments - w.e.f.-01/01/2018

Sr	Digital Rubber Hardness Tester	Unit Price
38	SHORE "A" RHT-A for Soft Rubber/Felt etc.	21200
39	SHORE "D" RHT-D for Hard Rubber/Plastic etc.	23500
Digital Metal (Leeb) Hardness Tester		
40	Hard Master HL-HRC-HRB-HRA-HB-HV-HS	48000
41	MI-970 HL-HRC-HRB-HRA-HB-HV-HS	49500
42	130 HL-HRC-HRB-HRA-HB-HV-HS	61000
43	Curvature Ring Set for HARDMASTER	16000
44	Impact Device 'D' (Probe) for MI 970	14000
45	Impact Device 'D' (Probe) for 130	36000
46	PC Interface RS 232C Software + USB Adaptor	6000
Digital Earth Resistance Tester		
47	DET 1501 (20/200/2000Ω)	9800
48	DET 1503 (20/200/2000Ω)	12400
Digital Insulation Tester (Megger)		
49	DIT 918 (100V/250V/500V/1000V/2500V-50GΩ)	6250
50	Hi Voltage Insulation Tester DIT 954 (1000V/2500V/5000V)	12200
51	Hi Voltage Insulation Tester DIT 3125A (Economical Model) (500V/1000V/2500V/5000V)	18200
52	Hi Voltage Insulation Tester DIT 3125 (500V/1000V/2500V/5000V-1000GΩ)	32000
Digital Lux Meter (Illuminometer)		
53	Lx 101A (1~2,00,000 Lux FC built in Photo Electric Sensor Pocket Type)	2100
54	Lx 101 (1~50,000 Lux Photo Electric Sensor)	2400
55	Lx 1330A (1~1,00,000 Lux)	3800
Digital Moisture Meter		
56	MM 2 (Pocket Type 2%~40% with 8 selection Range Multi Purpose)	1550
57	MM 2A+ (Pocket Type 2%~70% 4 Range Multi Purpose with Temperature/RH Measurement)	3320
58	MM-Wa (2%~70% Multi-Purpose Moisture Meter-Dual Probe)	6800
59	MM-W (High Accuracy 1%~80% Multi-Purpose Moisture Meter Dual Long Probe)	10400
60	MM-S (High Accuracy Multipurpose Non-Contact Moisture Meter)	11250
61	MM-S+ (Probe wide Application Multipurpose Dual Probe 0%~80% 10 range selection)	12500
62	GMM 7002A (High Accuracy Grain Moisture Meter 5%~ 30%)	6600
63	MM-G (High Accuracy Grain Moisture Meter 6%~30%, 36 Species Selection)	10800
64	MM-GC (High Accuracy Grain Moisture Meter 0%~50% Cup Type)	14500
Analog Multimeter		
65	HC 260TR TR test, AC/DC Volt DCA 2.5mA~10A, Ohm, -10DB~62DB NPN & Diode check	1600
Digital Multimeter		
66	9A 3¾	850
67	31 3½	950
68	31C 3½	1125
69	603 3½	1400
70	603A 3½	1700
71	14xL 3½	2250
72	451xL LCR	2950
73	16xL (6000 Analog Bargraph)	3200
74	18 True RMS (3 6/7, ACA/ACV, 6000 Count)	3600
75	DM 620 True RMS (50000 Count-Data Logger)	16500



	Digital Sound Level Meter	Unit Price
76	SL 4010 (30~130db) A&C Weighting (Pocket Type)	2200
77	SL 4001 (30~130db) A&C Weighting	4400
78	SL 4005 (30~130db) A&C Weighting P C Interface Compatible	5400
79	PC Interface RS 232C Software + USB Adaptor for SL 4005	4600
	Digital Surface Roughness Tester	
80	SURFTEST 10 (Ra:0.05-10.00um,Rz:0.020-100.0um)	67000
81	MICROSURF 10A (Ra:0.05-10.00um,Rz:0.020-100.0um)	69000
82	Precision Referance Standard (Test Piece) STEEL for MICROSURF 10A & SURFTEST 10	9600
83	Precision Referance Standard (Test Piece) GLASS for MICROSURF 10A & SURFTEST 10	16100
84	Standard Sensor for MICROSURF 10A & SURFTEST 10	30000
85	Extension Adaptor for MICROSURF 10A & SURFTEST 10	12200
86	PC Interface RS 232 Software + USB Data Interface Cable	6000
	Digital Gloss Meter	
87	GLS 09 (0.1~200 Gloss Units-Resolution 0.1 Gloss Units)	17500
88	GLS 09M (20°/60°/85° Combine Degrees Measuring Geometry)	28500
89	PC Interface Software + USB Data Interface cable for Gloss Meter	5600
	Digital Infrared Thermometer	
90	FH 1 Human Body Infrared Thermometer (30°C~45°C)	5490
91	MT 2A (-32°C~320°C)	1800
92	MT 4 (-50°C~550°C)	2100
93	MT 4xL (-32°C~550°C)	2500
94	MT 4A (-50°C~600°C)	3800
95	MT 4A+ (-50°C~750°C)	4400
96	MT 10A (-50°C~1000°C)	11000
97	MT 11 (-50°C~1100°C)	11500
98	MT 12A (-50°C~1150°C)	12500
99	MT 14 (-50°C~1350°C)	14500
100	MT 16 (-18°C~1650°C)	32600
101	MT 18 (-30°C~1850°C)	31000
102	MT 18xL (-18°C~1850°C) (RS 232 compatible)	39200
103	MT 22 (200°C~2500°C)	52000
	Digital Thermo-Humidty Meter (Thermo Hygrometer)	
104	TH 01 (-10°C~70°C, Humidity 20%~90% RH Indoor)	1250
105	TH 01 (-10~70°C Indoor, -50~70°C Outdoor, Humidity 20%~90%) RH	1340
106	HT 3006 (-40°C~1400°C, Humidity 5%~90% RH)	2400
107	HT 9 Large Back light LCD -10~60°C, 10%~95%, Wet Bulb Temperature -10~60°C	5950
108	HT 9A Data Logger Large Bk light Dual Display LCD -30~80°C, 0%~100% Dew point pick up	6360
	Digital Tachometer	
109	DT 2234 B (Non-Contact Laser 2.5~99,999RPM)	2250
110	DT 2235 B (Contact Tachometer 0.5~19,999RPM)	2600
111	TM 1000xL (Non-Contact Laser Tachometer 999 second Counter 0.5~99,999RPM)	2800
112	TM 4005 (Contact/Non-Contact Combine)	5250
113	TM 5000P (Non-Contact/Contact Multifunctional Tachometer with Extended Cable Probe)	14200
114	"LT" DT 2236 (Photo/Contact Combine)	3600



Sr	Analog Tachometer	Unit Price
115	"H" (HUSTLER TYPE) 0-10000RPM "FUJI" Brand	22000
116	"H" (HUSTLER TYPE) 0-10000RPM "TECLOCK" Brand	26800
Digital Ultrasonic Thickness Gauge		
117	UTG 5 (1.2 ~ 220mm Resolution 0.1mm)	13400
118	UTM 5A (1.2 ~ 225mm Resolution 0.1mm)	13800
119	UTM 5 (1 ~ 200mm Resolution 0.1mm)	16500
120	UTM 9 (0.9~350mm Resolution 0.01mm)	21500
121	UTG 27 (1~400mm Resolution 0.01mm)	26000
122	UTM 18CT (0.65~600mm Resolution 0.01mm) through Coating Thickness	54060
123	Spare Probe Standard for UTM 5/UTM 9/UTG 27	4800
124	Spare Probe 6mm for UTM 5/UTM 9/UTM 5A/UTG 27	6000
125	High Temperature Ceramic Probe for UTM 5/UTM 9/UTG 27	14000
126	Spare Probe for UTM 18CT (1.0-600mm Thickness Probe) No 5	6000
127	Spare Probe for UTM 18CT (3-30mm Through Coating Probe) P 5EE	6200
128	Spare Probe for UTM 18CT (0.65-200mm Thickness Probe) No 7	7600
129	PC Interface RS 232C Software + USB Adaptor for UTM 5 & UTM 9	4800
130	PC Interface RS 232C Software for UTM 18CT	8200
131	Calibration Step Block for Ultrasonic Thickness Gauge 4 Steps	16000
Digital Vibration Meter		
132	VM 8200P (Portable Shear Type)	14500
133	VM 8200+ (Velocity, Acceleration & Displacement)	19100
134	VM 8200+MK II (Velocity, Accele., Displacement, RPM & Frequency)	24500
135	VB 8202A (Velocity, Accele., Displacement, RPM & Frequency)	30500
136	PC Interface RS 232C Software + USB Suitable for VM 8200+/VM 8200+mk II/VB 8202A	6000
137	Spare Probe for Vibration Meter	9800
138	Spare Attachment rare Earth Powerful Magnet/Stinger Probe Spherical / Cone	5000
139	Spare Piezo Electric Pin Probe for VM 8200+/VM 8200+mk II/ VB 8202A	14000
Digital Capacitance Meter		
140	DCM 1501 (0.1pF~20,000 µF)	1880
Digital Angle Gauge		
141	Angle Gauge AG 900 Working range angle: 0°~225° Angle precision: ±0.5°, Resolution: 0.1°. 400mm with Horizontal & Vertical Glass bubble can be used as Spirit Level	3050
Pocket Thickness Gauge		
142	Peacock Brand JAPAN Mod: PS 1 0-20mm x0.1mm	3600
143	Peacock Brand JAPAN Mod: CS 10 0-10mm x 0.01mm	5400
Digital Stroboscope		
144	DT 2239 (50~12000FPM)	12000
145	DT 2259A (50~40000FPM)	15500