



Pricelist October 2021

Electrical & Electronic Test Measuring Instruments

Metrixplus Price List Effective OCTOBER 2021

(This Price-List Supersedes all Previous Price-List)

INFRARED THERMOMETER, HSN : 90251990

| | | | |
|---|---------------|---|--------|
| 1 | FH 2 | Human Body Infrared Thermometer 30°C~45°C (86°F~113°F) | 3,000 |
| 2 | MT 2-C | Non-contact Infrared Thermometer -50°C ~ 380°C (-58°F~716°F), DS 12: 1, Emissivity 0.95 fixed, Color Display | 1,200 |
| 3 | MT 4xL | Non-contact Infrared Thermometer -32°C~550°C (-26°F~1022°F), DS 12:1, Emissivity 0.95 fixed, Gift box+Carry case | 1,600 |
| 4 | 62 Pro | Non-contact Infrared Thermometer -50°C ~ 650°C (-58°F~1202°F), DS 12:1, Emissivity 0.1~1.00 Adjustable, color screen, circular laser. | 3,000 |
| 5 | 65 Pro | Non-contact Infrared Thermometer -50°C ~ 850°C (-58°F~1202°F), DS 12:1, Emissivity 0.1~1.00 Adjustable, K-type thermocouple, color screen, circular laser | 3,800 |
| 6 | MT 12A | Non-contact Infrared Thermometer -18°C~1150°C (-58°F~2102°F), DS 20:1, Emissivity 0.10~1.00 Adjustable | 7,600 |
| 7 | MT 16 | Non-contact Infrared Thermometer -18°C~1650°C (-58°F~3002°F), DS 50:1, Emissivity 0.10~1.00 Adjustable | 12,000 |
| 8 | MT 18 | Non-contact Infrared Thermometer 200°C~1850°C (-22°F~3362°F), DS 50:1, Emissivity 0.10~1.00 Adjustable | 25,000 |
| 9 | MT 22 | Data Logger, Non-contact Infrared Thermometer 200°C~2500°C (0°F~2462°F), DS 80:1, Emissivity 0.1~1 Adjustable | 27,000 |

DIGITAL THERMOMETER/HUMIDITY METER(HYGROMETER), HSN : 90251990

| | | | |
|----|-----------------|--|-------|
| 10 | TH 01 | Humidity/Temperature - 10°C~ 70°C (C/F) RH: 20% ~ 90%. Indoor | 500 |
| 11 | HT 9A | Data Logger Temperature Humidity Meter Large Backlight LCD dual display - 30°C~80°C (C/F) RH: 0% ~ 100% Dew Point pickup | 4,000 |
| 12 | HT 9 | Temperature Humidity Meter Large Backlight LCD display - 10°C~ 60°C Wet Bulb -10 ~ 60°C (C/F) RH: 10% ~ 95% | 4,400 |
| 13 | DT 305-S | High Precision Thermometer , K type Thermocouple, -50°C~1300°C (standard probe : -50 ~ 250°C), data storage, Auto Power Off, alarm indication (HSN: 90251910) | 1,100 |

DIGITAL CLAMP ON POWER METER, HSN : 90303900

| | | | |
|----|---------------|---|-------|
| 14 | 3510PW | Data Logger Power clamp Meter Display Backlight LCD 9999 auto range ACV, ACA, Active Power, apparent power, reactive power, power factor, phase angle, active energy, AC true RMS, 55mm Jaw caliber | 9,000 |
|----|---------------|---|-------|

DIGITAL ACA/DCA CLAMP METER, HSN : 90303900

| | | | |
|----|--------------|--|-------|
| 15 | 725A+ | True RMS 5999 digit backlight LCD DC/AC 600A ACV/DCV, resistance, Frequency, capacitance, duty, Temperature, Diode, continuity, APO | 3,600 |
| 16 | 4250T | True RMS 3999 digit DC/AC 1000A ACV/DCV, resistance, Frequency, capacitance, duty, Temperature, Diode, continuity, APO | 4,800 |
| 17 | 2003 | 1999 digit Panel Calibrate , Backlit, DC/AC 2000A , ACV/DCV, Resistance, Continuity, Diode, Data Hold | 5,200 |

DIGITAL ACA CLAMP METER, HSN : 90303900

| | | | |
|----|--------------|--|-------|
| 18 | 125A+ | 1999 digit backlight LCD AC 600A ACV/DCV, resistance, Diode, continuity, data hold | 1,400 |
| 19 | 225A+ | 3999 digit backlight LCD AC 600A True RMS ACV/DCV, resistance, capacitance, frequency, temperature, diode, continuity, data hold, NCV | 2,000 |
| 20 | 1250A | 1000A AC 1999 digit ACV/DCV, Resistance, Diode, Continuity, Data Hold, APO | 2,200 |
| 21 | 2250T | True RMS 1000A AC, 33/4 digit, inrush, ACV/DCV, Resistance, Capacitance, Frequency, Duty, Temperature, Diode, Continuity, Data Hold, APO | 2,500 |

DIGITAL MULTIMETER, HSN : 90303100

| | | | |
|----|-----------------|---|--------|
| 22 | 31 | 3½ Digit backlight LCD display ACV/DCV, DCA, Resistance, Diode, Continuity, Battery Test | 800 |
| 23 | 31C | 3½ Digit backlight LCD display ACV/DCV, DCA, Resistance, Diode, Continuity, Temperature | 900 |
| 24 | 603+ | 3½ Digit ACV/DCV, ACA/DCA, Resistance, Capacitance, Frequency, Diode, Continuity, hFe Transistor, Phase wire test, I R Remote test , Data Hold, APO | 1,300 |
| 25 | 603A+ | 3½ Digit ACV/DCV, ACA/DCA, Resistance, Capacitance, Frequency, Diode, Continuity, hFe Transistor, Phase wire test, I R remote test , Temperature, Data Hold, APO | 1,600 |
| 26 | 171TRMS+ | True RMS 6000 count , Large Backlit LCD Display, flashlight, AC/DC V, AC/DC A, resistance, capacitance, temperature, frequency, duty ratio, hFe, diode, continuity, NCV test, data hold, APO. | 2,500 |
| 27 | 451 | Panel Calibrate LCR Multimeter 3½ digit Extra large Backlight LCD display ACV/DCV, ACA/DCA, Resistance, Capacitance, Frequency, Inductance, diode, continuity, transistor HFe, APO | 2,400 |
| 28 | DM 620 | 50000 count DATA LOGGER True RMS 18000 point Data memory, 10Mhz Frequency Counter, auto calibration, USB to PC, 1000V AC/DC, ACA/DCA, resistance, capacitance, frequency, duty, temperature, Diode, continuity, real time clock, Full Range overload | 14,000 |

ANALOG MULTIMETER, HSN : 90303100

| | | | |
|----|----------------|--|-------|
| 29 | HC260TR | TR test, AC/DC Volt DCA 2.5mA ~ 10A, Ohm, -10DB ~ 62DB NPN & Diode check | 1,000 |
|----|----------------|--|-------|

DIGITAL CAPACITANCE METER, HSN : 90303330

| | | | |
|----|-----------------|---|-------|
| 30 | DCM 1501 | Digital capacitance meter wide measuring range in 9 steps 200pF ~ 20mF | 1,800 |
|----|-----------------|---|-------|

DIGITAL INSULATION TESTER, HSN : 90303390

| | | | |
|----|----------------------|---|--------|
| 31 | DIT 918 | Large Backlight LCD display Heavy Duty 100V/250V/500V/1000V/2500V 50GΩ , AC/DC Voltage Insulation Tester | 5,000 |
| 32 | DIT 3125A Eco | Large Backlight LCD, Heavy duty 500V/1000V/2500V/5000V 1000GΩ Insulation Tester, AC/DC Voltage, PI measurement, Timer, with external power(adaptor) | 17,400 |

DIGITAL EARTH RESISTANCE TESTER, HSN : 90303900

| | | | |
|----|-----------------|---|-------|
| 33 | DET 1501 | Large LCD 3 ½ Digit Max. 1999.Auto Range 0~ 2000Ω Accuracy Earth Resistance: ±2%rdg±0.1Ω (20Ω) ±2%rdg±3dgt (200Ω/2kΩ) | 6,400 |
| 34 | DET 1503 | Jumbo backlight LCD Display Heavy duty Measuring Range: 0.00~20Ω / 0.0~200Ω / 0~2000Ω high accuracy ±2%rdg±0.1Ω (20Ω) ±2%rdg±3dgt (200Ω/2000Ω) Timer | 9,000 |

LASER DISTANCE METER, HSN : 90318000

| | | | |
|----|---------------|---|-------|
| 35 | DM 40 | Laser Distance Meter, 0.05~40m metric/imperial measurement, area/volume/pythagorean calculatiion, data storage, dual axis spirit level | 2,400 |
| 36 | DM 60 | Laser Distance Meter, 0.05~60m metric/imperial measurement, area/volume/pythagorean calculatiion, data storage, dual axis spirit level | 3,400 |
| 37 | DM 100 | Laser Distance Meter, 0.05~100m metric/imperial measurement, area/volume/pythagorean calculatiion, data storage, dual axis spirit level | 5,600 |

DIGITAL STROBOSCOPE, HSN : 90292030

| | | | |
|----|-----------------|---|--------|
| 38 | DT 2239 | 50~12000FPM Internal / external triggering; x2 and ÷2 button for fast adjustment. | 11,200 |
| 39 | DT 2259A | 50~40000FPM Internal / external triggering; x2 and ÷2 buttons for fast adjustment. | 13,600 |

DIGITAL TACHOMETER, HSN : 90292010

| | | | |
|----|------------------|---|-------|
| 40 | DT 2234BL | Non Contact Type Laser Tachometer, 2.5~99,999rpm , Large Backlit LCD Display | 1,600 |
| 41 | TM 1000xL | Large Back light LCD non-contact Laser Tachometer 999 second Counter(REV) 0.5~99,999RPM | 2,400 |
| 42 | DT 2235BL | Contact type tachometer, 0.5 ~ 19,999 rpm , large backlit lcd display | 2,000 |
| 43 | TM 4005 | Contact/non-contact Combine Tachometer | 4,200 |

DIGITAL ANEMOMETER, HSN : 90318000

| | | | |
|----|---------------|---|-------|
| 44 | AVM 01 | Large Backlit LCD Display 0.3~30M/S & Air Temperature 0~50°C Fan type Built in Probe (Pocket Type) | 1,400 |
| 45 | AVM 03 | 0.4~30M/S & Air Temperature C/F 0~60°C / 32~140°F Fan type Vane Probe | 3,200 |
| 46 | AVM 05 | Large backlit LCD Display 0.4~45M/S CMM,CFM & Air Temperature C/F0~60°C / 32~140°F Fan type Vane Probe Optional Data Logger via PC interface | 4,400 |
| 47 | | PC Interface RS 232C + USB Adapter + Software for AVM 05 | 3,150 |

DIGITAL SOUND LEVEL METER, HSN : 90278090

| | | | |
|----|----------------|---|-------|
| 48 | SL 4001 | Large backlit LCD Display 30~130db Fast/ Slow weighing A & C | 2,800 |
| 49 | SL 4005 | Large backlit LCD Display 30~130db Fast/ Slow weighing A & C or "F" Flat built in calibration signal 94db LP, LEQ, LN. 30 Group memory, Data logger via RS 232 interface + | 4,400 |
| 50 | | PC Interface RS232C + Software + USB Adaptor for SL 4005 | 3,150 |

DIGITAL LUX METER(ILLUMINOMETER), HSN : 90278090

| | | | |
|----|------------------|--|-------|
| 51 | LX101+ | 1~2,00,000 Lux , Separate Photo Electric sensor | 1,500 |
| 52 | LX 1330A+ | 0~1,99,900 Lux , Lux/FC conversion, 360° rotatable head sensor , max/min, data hold, backlit LCD | 2,800 |
| 53 | LX 1336A | 0~5,00,000 Lux , 0~20,000 FC , Separate Light Sensor, PC interface , In built low battery indicator, Max value hold function. | 6,600 |

DIGITAL COATING THICKNESS GAUGE(DFT METER), HSN : 90173029

| | | | |
|----|--------------------------|---|--------|
| 54 | CG 3000 | Wet film comb to measure wet film thickness 0 ~ 3000um | 500 |
| 55 | Coat Gauge F xL | Integrated Probe 0 ~ 1500um Only Ferrous Large Display, V-groove, Zero and multi point calibration, um/mil, single and continuous mode operation | 8,800 |
| 56 | Coat Gauge FN xL | Integrated Probe 0 ~ 1500um Ferrous & Non Ferrous Combine Large Display, V-groove, Zero and multi point calibration, um/mil, single and continuous mode operation | 10,400 |
| 57 | Coat Gauge Pro | Integrated Probe 0 ~ 2000um Ferrous & Non Ferrous Combine , Bluetooth, smart color display, trend graph, calibration guide, data memory, statistics | 18,400 |
| 58 | Coat Scope i | Integrated Probe 0 ~ 2000um Ferrous/non-ferrous combine optional data logger via PC Interface RS 232, memory, statistics | 26,600 |
| 59 | Coat Measurer F | External Probe Large backlit LCD display 0 ~ 1250um Only Ferrous optional data logger via PC Interface RS 232 | 14,200 |
| 60 | Coat Measurer F+N | External Probe Large backlit LCD display 0~1250um Ferrous/non-Ferrous Combine optional data logger via PC interface RS 232 | 18,800 |
| 61 | Coat Scope Pro | External Probe 0 ~ 2000um Ferrous & Non Ferrous Combine , Bluetooth, smart color display, trend graph, calibration guide, data memory, statistics | 20,400 |
| 62 | Coat Scope 27 | External Probe Large backlit LCD Display high accuracy and in built 99 group memory 0~2000um ferrous/non-ferrous combine optional data logger via PC Interface RS 232 | 26,400 |
| 63 | Coat Scope 27 4K | External Probe Large backlit LCD Display high accuracy and in built 99 group memory 0~4000um ferrous/non-ferrous combine optional data logger via PC Interface RS 232 | 27,400 |
| 64 | Coat Scope 27 5K | External Probe Large backlit LCD Display high accuracy and in built 99 group memory 0~5000um ferrous/non-ferrous combine optional data logger via PC Interface RS 232 | 32,000 |
| 65 | | Spare 'Fe' Probe | 3,150 |
| 66 | | Spare 'Fe+'nFe' Combine Probe | 3,750 |
| 67 | | Spare Calibration Foil Set (5 pc. Foil) | 1,300 |
| 68 | | PC Interface(Cable + Software) for Coat Measurer series/Coat Scope series | 3,750 |

COLOR METER, HSN : 90318000

| | | | |
|----|---------------|---|--------|
| 69 | COL 45 | Measurement and difference calculations in 6 color spaces , (L*,a*,b*), (L*, C*ab, hab), (Y, x, y), (X, Y, Z), (Rs, Gs, Bs) or (WI, YI, Tw), data storage, statistics display, tolerance limit set | 26,400 |
|----|---------------|---|--------|

ULTRASONIC THICKNESS GAUGES, HSN : 90173029

| | | | |
|----|----------------|---|--------|
| 70 | UTM 5A+ | Color LCD backlit display with menu operation, 1~300mm , Resolution 0.1mm/0.01mm/0.01inch selectable, velocity 1000~9999m/s, data storage , max/min/avg | 11,600 |
| 71 | UTM 5 | Large backlit LCD display 1~200mm Resolution 0.1mm velocity 500~9000m/s. | 15,600 |
| 72 | UTM 9 | Large backlit LCD display 0.9~350mm high Resolution 0.01mm velocity 500~9000m/s. | 19,000 |
| 73 | UTG 27 | Metal body Large backlit LCD display 1.0~400mm Resolution 0.1/0.01mm switchable velocity 500~9000m/s | 21,600 |
| 74 | | Spare probe 6mm/5mHz for small objects suitable for Mod: UTM 5/UTM 9/UTG 27 | 3,750 |
| 75 | | Spare Probe Standard(8mm) suitable for UTM 5/UTM 9/UTG 27 | 3,150 |
| 76 | | High Temperature Ceramic Probe suitable for Mod: UTM 5/ UTM 9/UTG 27 | 9,300 |
| 77 | | Calibration Step Block for Ultrasonic Thickness Gauge 4 steps / 7 steps for mm / 4 steps for inch | 10,750 |
| 78 | | PC Interface(Software + Cable) for UTM 5/ UTM 9/ UTG 27 | 3,750 |

ULTRASONIC LEAKAGE DETECTOR, HSN : 90318000

| | | | |
|----|---------------|--|--------|
| 79 | ULD 30 | Locate the source of ultrasonic emissions generated by gas or air leaks, LED indication and audible tone. | 29,000 |
|----|---------------|--|--------|

DIGITAL VIBRATION METER, HSN : 90318000

| | | | |
|----|----------------------|--|--------|
| 80 | VM 8200P | Piezoelectric ceramic(shear type),portable,easy on site vibration measurement. Backlit LCD Display,Acceleration,Velocity, Displacement,wide frequency range 10Hz~15KHz in acceleration mode | 14,000 |
| 81 | VM 8200+ | High Accuracy,easy onsite vibration measurements.Backlit LCD display Velocity, Acceleration, Displacement wide Frequency range 10Hz ~10kHz in acceleration mode. Data Logger via RS 232 or USB. | 19,600 |
| 82 | VM8200 mk II+ | High Accuracy,heavy metal body,easy onsite vibration measurement. Backlit LCD display,Velocity, acceleration, displacement, RPM, wide frequency range 10Hz~10kHz acceleration mode.Data logger via RS 232 or USB | 24,600 |
| 83 | VB 8202A | High Accuracy,heavy metal body,easy onsite vibration measurement. Backlit LCD display,Velocity, acceleration, displacement,all can be displayed simultaneously,wide frequency range 1Hz ~ 10kHz in acceleration mode.Data logger via RS 232 or USB | 28,800 |
| 84 | | Spare piezo electric sensor probe | 6,300 |
| 85 | | Spare piezo electric Pin probe for VM 8200+/VM 8200mk II/ VB 8202A | 9,300 |
| 86 | | Spare Attachment rare earth powerful Magnet/stinger probe Spherical / cone | 3,150 |
| 87 | | PC Interface(Cable + Software) for VM 8200+/VM 8200mkII+/VB 8202A | 4,600 |

DIGITAL GLOSS METER, HSN : 90318000

| | | | |
|----|-------------------|--|--------|
| 88 | GLS 09 | High accuracy.Large backlit LCD display, 60°angle 200GU used to test Glossiness in various industries i.e. Automobile, paint, paper, paper printing, coating, ink, metal, artificial leather, electroplate, electronics, ceramic, hardware, furniture, granite etc.Data logger via USB | 15,200 |
| 89 | GLS 09M | Multi Angle 20°/60°/85° .200GU .High accuracy.Large backlit LCD display used to test Glossiness in various industries i.e. Automobile, paint, paper, paper printing, coating, ink, metal, electroplate, electronics, ceramic, hardware, furniture, granite marble etc. Data logger via USB. | 26,000 |
| 90 | Microgloss | Multi Angle, High Precision, Data Logger Gloss Meter 20°/60°/85° .1000 GU range.Widely used to test glossiness in these industries, such as automobile, paint, ink,coating,wood products; marble, granite, vitrified polished tile, pottery brick etc. PC interface. | 60,000 |

| | | | |
|----|--|---|-------|
| 91 | | PC Interface(Cable + Software) for GLS 09/09M | 4,000 |
|----|--|---|-------|

DIGITAL RUBBER / METAL(LEEB) HARDNESS TESTER, HSN : 90248091

| | | | |
|----|---------------------|--|--------|
| 92 | RHT -A | Large backlit LCD display Shore 'A' 0~100A/10~90H for soft Vulcanize rubber, natural rubber, nitriles, thermoplastic elastomers, flexible poly acrylics and thermosets, wax, felt, etc Data logger via USB | 19,200 |
| 93 | RHT -D | Large backlit LCD display Shore 'D' 0~100/10~90H for Hard Rubber, thermoplastic elastomers, harder plastics, and rigid thermoplastics etc. Data logger via USB | 16,000 |
| 94 | Hardmaster-P | Backlit 128*64 matrix display. 170~960HLD ,converts to all common hardness scales HV, HB,HRC, HRB, HRA, HS.Memory of 600 groups data.Inbuilt software calibration, PC interface for Data logging, directly print with mini printer(optional) . | 31,600 |
| 95 | LHT 1 | Pen type Backlit 128*332 matrix display. 170~960HLD ,converts to all common hardness scales HV, HB,HRC, HRB, HRA, HS.Memory of 600 groups data.Inbuilt software calibration | 37,000 |
| 96 | | Curvature RING SET for Hardness Tester | 9,300 |
| 97 | | Impact Device 'D' (Probe) for MI 970 | 7,900 |
| 98 | | PC Interface(Cable + Software) for RHT A/ RHT D/ Hardmaster/ MI-970 | 3,750 |

DIGITAL SURFACE ROUGHNESS TESTER, HSN : 90318000

| | | | |
|-----|----------------------|--|--------|
| 99 | Microsurf 10A | Large backlit LCD display,multi parameters measured Ra, Rz, Rt, Rq .Widely used in production site to measure surface roughness of various machine-processed parts.High accuracy Inductive Transducer, easy operation. Can store the latest 7 groups measurements | 68,000 |
| 100 | Surftest 10 | Large backlit LCD display.Parameters measured Ra, Rz .Widely used in production site to measure surface roughness of various machine-processed parts.High accuracy Inductive Transducer, easy operation. Can store the latest 7 groups measurements. | 72,000 |
| 101 | | Sensor for Surface Roughness Tester | 25,750 |
| 102 | | Precision reference Standard(Test piece) STEEL for MICROSURF 10A & SURFTEST 10 | 6,300 |
| 103 | | Precision reference Standard(Test piece) GLASS for MICROSURF 10A & SURFTEST 10 | 7,900 |
| 104 | | Extension Adapter Sleeve for MICROSURF 10A & SURFTEST 10 | 9,300 |
| 105 | | PC Interface(Software + Cable) | 4,000 |

DIGITAL MOISTURE METER, HSN : 90318000

| | | | |
|-----|----------------|--|--------|
| 106 | MM 2 | Pocket type 2%~40% large LCD display Wood purpose moisture meter 8 selection range max/min set data hold & APO | 1,400 |
| 107 | MM 2A+ | Pocket type.Large backlit LCD display, 2%~70% four range Multipurpose moisture meter with Temperature & RH measurement.Data hold & APO. | 2,200 |
| 108 | MM-Wa | Large backlit LCD display. 2%~70% four range dual Probe with Temperature & RH measurement. Multi purpose moisture meter ,wide application,Data Hold & APO. | 5,200 |
| 109 | MM-W | Intelligent high accuracy,wide application, multi purpose moisture meter with Dual Probe ,backlit LCD display 0%~80% with 10 selection ranges . Long sensor can measure various substrates data hold & APO. | 8,800 |
| 110 | MM-S | intelligent,wide application, multi purpose non-contact moisture meter ,backlit LCD Display, 0%~80%,20 range substrates selection non-destructive used for marble, granite idols handicrafts etc.Data hold APO. | 9,000 |
| 111 | MM-S+ | Probe ,intelligent,wide application,multipurpose dual probe 0%~80%,10 range selection ,can measure non-contact and contact with pin probe data hold & APO. | 9,200 |
| 112 | MM-P | Paper moisture meter for paper products, separate flexible probe, data storage, statistics display, LED indication | 13,600 |
| 113 | MM-SOIL | Moisture content in soil, agricultural purposes, 0 ~ 80% , separate flexible probe, data storage, statistics display, LED indication | 13,200 |

| | | | |
|-----|------------------|---|--------|
| 114 | GMM 7002A | 5%~30% 4 species selection backlit LCD Display with temperature measurement. Grain Moisture Meter Hi-Lo alarm setting data hold & APO. | 4,200 |
| 115 | MM-G | Intelligent,high accuracy, 6%~30% ,backlit LCD display, 36 species selection.Grain Moisture Meter ,automatic temperature compensation and auto calibration,hi-lo alarm setting,data hold & APO. | 9,600 |
| 116 | MM-GC | Grain Moisture Meter new spring type cup design for better accuracy ,large backlit LCD Display,high accuracy , 0%~50% , 22 species selection ,can store 240 group memory,automatic calibration and temperature compensation data hold APO. | 14,000 |
| 117 | | PC Interface(Software + Cable) for MM-W/ MM-S/ MM-S+/ MM-SOIL/ MM-G/ MM-GC | 3,750 |

DIGITAL POWER GUARD, HSN : 90303900

| | | | |
|-----|--------------|---|-------|
| 118 | PG 08 | Power Guard , Large backlight LCD Watt/CUR/Volt/Freq/EC/CO2/PF displayed in sequence | 1,400 |
|-----|--------------|---|-------|

VOLTAGE TESTER(PEN TYPE), HSN : 90303900

| | | | |
|-----|-------------|---|-----|
| 119 | CD 1 | Line VoltageTester 90V~1000V , buzzer and light indication | 300 |
| 120 | CD 2 | Pen type VoltageTester 24V~600V | 500 |
| 121 | CD 3 | Pen type VoltageTester 12V~1000V , bar display and buzzer, changeable sensitivity | 800 |

ANGLE GAUGE, HSN : 90173029

| | | | |
|-----|---------------|---|-------|
| 122 | AG 900 | Digital Angle Gauge , 400mm Horizontal & Vertical, 0°~225°, Backlit LCD, Glass bubble can be used as spirit level, APO | 2,600 |
|-----|---------------|---|-------|

FSK PRECISION LEVEL, HSN : 90153090

| | | | |
|-----|-------------------|--------------------------------------|-----|
| 123 | Flat 4" | 100mm, 0.02m/mm sensitivity, 0.9kgs | POR |
| 124 | Flat 6" | 150mm, 0.02m/mm sensitivity, 1.3kgs | POR |
| 125 | Flat 8" | 20mm, 0.02m/mm sensitivity, 1.8kgs | POR |
| 126 | Flat 12" | 300mm, 0.02m/mm sensitivity, 3.3kgs | POR |
| 127 | Square 4" | 100mm, 0.02m/mm sensitivity, 1.6kgs | POR |
| 128 | Square 6" | 150mm, 0.02m/mm sensitivity, 3.4kgs | POR |
| 129 | Square 8" | 20mm, 0.02m/mm sensitivity, 5.0kgs | POR |
| 130 | Square 12" | 300mm, 0.02m/mm sensitivity, 10.0kgs | POR |

ANALOG TACHOMETER, HSN : 90318000

| | | | |
|-----|-----------------|---|-----|
| 131 | FUJI "H" | 0-10000 RPM analog tachometer with peripheral speed measurement | POR |
|-----|-----------------|---|-----|

Terms

Ex-Pune prices

This Price-List Supersedes all Previous Price-List

GST applicable @ 18%

We look forward to your valuable orders

Metrix**+**TM

ELECTRICAL AND ELECTRONIC TEST MEASURING INSTRUMENTS

