



PROFILE PROJECTORS



ISP-Z3015



ISP-A1000E

digital readout of **ISP-A1000E**

- touch buttons
- USB data output to Excel and CAD
- show diagram




software flash disk
(included, only for
ISP-A1000E)


OPTIONAL ACCESSORY



lens



rotary table
(glass plate diameter 100mm)



overlay chart (protractor with 1°
graduation, radius with 1mm increment)



holder with clamp



swivel center support



V-block set



50mm reading scale
(check magnification accuracy)



300mm calibration scale (check
magnification accuracy together
with 50mm reading scale or
calibrate measuring accuracy)



green/yellow filter


















demo sample



printer (only for **ISP-A1000E**)

SPECIFICATION

Code		ISP-Z3015		ISP-A1000E		
Edge detector		not included		included		
Lens	magnification	10X (included)	20X (optional)	50X (optional)	100X (optional)	
	view field	Ø30mm	Ø15mm	Ø6mm	Ø3mm	
	working distance	77.7mm	44.3mm	38.4mm	25.3mm	
Max. workpiece height		90mm	90mm	90mm	90mm	
Magnification accuracy		±0.08%				
Image		erect image				
Projector screen		diameter: Ø300mm				
		rotation range: 0°~360°, resolution: 1" or 0.01°				
		reference lines: cross-hairs				
Stage	metal stage size	340×152mm				
	glass stage size	196×96mm				
	X-Y stage travel	range: 150×50mm				
		resolution: 0.5µm				
		accuracy: (4+L/25)µm L is the measuring length in mm				
	Z (focus) travel range	90mm				
max. load capacity	4kg					
Illumination		contour illumination: 24V/150W halogen lamp, brightness is adjustable				
		surface illumination: 24V/150W halogen lamp				
Data processing unit	display	X-Y stage travel, screen rotation				
	output	RS232C		RS232C, USB (data output to Excel and CAD)		
	function		measure coordinate of point			measure coordinate of point
			measure coordinate of line			measure coordinate of line
			measure center coordinate, radius of circle with three points			measure center coordinate, radius of circle with three points
			measure distance between two objects			measure distance between two objects
			measure angle with four points or two lines			measure angle with four points or two lines
			set origin of coordinate			coordinate transform
			coordinate transform			choose measurement object automatically according to the selective point and display the result
			set midpoint of coordinate			
advanced function	—		programming for batch measurements			
Power supply		110/220V, 50/60Hz				
Dimension (L×W×H)		550×770×1100mm				
Weight		135kg				

STANDARD DELIVERY

Main unit	1 pc
10X lens with half-reflection mirror and oblique illuminator mirror	1 pc
Overlay chart clip	4 pcs
Foot-switch	1 pc
Anti-dust cover	1 pc
Blue filter	1 pc
Software (only for ISP-A1000E) and USB cable	1 pc

OPTIONAL ACCESSORY

20X lens with half-reflection mirror and oblique illuminator mirror	ISP-A1000-LENS20X
50X lens with half-reflection mirror	ISP-A1000-LENS50X
100X lens with half-reflection mirror	ISP-A1000-LENS100X
Rotary table	ISP-A1000-TABLE
Overlay chart	ISP-A1000-CHART
Holder with clamp	ISP-A1000-HOLDER
Swivel center support	ISP-A1000-SUPPORT

V-block set	6896-12
50mm reading scale	ISP-A1000-SCALE50
300mm calibration scale	ISP-A1000-RULE
Green filter	ISP-A1000-GR-FILTER
Yellow filter	ISP-A1000-YE-FILTER
Demo sample	ISP-A1000-DEMO
Printer (only for ISP-A1000E)	ISP-A1000-PRINTER